



ARIES TECH 2



Air cooled water chillers featuring hermetic scroll compressors with R410A.

Nominal cooling capacity 164 – 945 kW



The new generation of commercial chillers.

The air-cooled water chillers ARIES Tech 2 is the answer to the present and future needs of commercial air conditioning systems. Preserving their versatility and reliability, they already meet the seasonal energy performance requirements of the ErP Regulation EcoDesign.

They are extremely customizable to guarantee an easy installation for any plant solution.

The ARIES Tech 2 range is the example of targeted design, essential to obtain a reduced operating cost for air conditioning of medium and large residential or commercial spaces without excluding reliability the environment protection.



Cooling, conditioning, purifying.

Benefits

- The ARIES TECH 2 range already meet the limits set by the ErP, for the index SEER (Tier 2 01/01/2021);
- Wide operating limits for starting up and functioning even in the worst conditions;
- Wide range of options and kits for easy installation;
- Easy access to all components;
- Advanced electronic control with integrated web server.

Options

- Low water temperature version (down to -10 °C outlet water temperature);
- Low ambient temperature version (down to -20 °C);
- Stainless steel shell and tube evaporator;
- Single or twin water pump with low or medium head pressure;
- Water accumulation tank;
- IN/OUT compressors valves;
- High efficiency EC brushless fans (base equipment for SSN version);
- Total heat recovery;
- Protection coating for condenser coils, suitable for installation in aggressive environments;
- Microchannels condenser coils;
- Antifreeze heaters for heat exchangers and hydraulic module (if included);
- Metallic mesh filters for condenser coils protection;
- Soundproof jacket or housing for compressors (for HE configuration);
- Soft start for compressors to reduce by 20% the unit's inrush current.

Standard Features

- Refrigerant R410A;
- 4, 6 or 9 scroll compressors on two or three independent refrigerant circuits;
- Crankcase heater compressor and phase-monitor;
- Victaulic hydraulic connections kit (supplied as standard with each unit);
- Electronic expansion valve;
- Axial fans configured with protective grilles and sickled bladed with die-cast aluminium airfoil profiled;
- Electrical cabinet protection rating IP54;
- Refrigerant charge, non-freezing oil and tests performed in the factory;
- Electronic microprocessor controller with high computing capacity and an easy to use graphical interface;
- Modbus RS485 serial output for connection to supervision systems;
- Master/slave configuration manageable between 2 units.

Kits

- Antivibration mounting;
- Metallic mesh filters kit for condenser coils protection;
- Replicated remote user terminal kit;
- Supervision system xWEB300D EVO;
- Modularity kit for xDRIVE (master/slave from 3 to 8 units).

Acoustic configurations

- HE - basic acoustic configuration;
- SHE - low noise acoustic configuration;
- SSN - very low noise acoustic configuration.

Models AST2	065			075			090			105			115			140		
Versions	HE	SHE	SSN	HE	SHE	SSN	HE	SHE	SSN	HE	SHE	SSN	HE	SHE	SSN	HE	SHE	SSN
Nominal cooling capacity (1)	163,9	157,9	150,1	187,2	178,0	171,0	219,1	206,4	196,6	270,9	258,6	249,0	307,1	289,5	277,0	360,1	333,6	319,8
Total absorbed power (1)	66,1	67,0	70,6	68,6	70,4	72,9	82,6	86,5	90,7	93,2	94,7	97,5	111,5	116,1	120,9	139,7	150,5	156,9
EER (2)	2,48	2,36	2,12	2,73	2,53	2,34	2,65	2,39	2,17	2,91	2,73	2,55	2,75	2,49	2,29	2,58	2,22	2,04
SEER (3)	4,19	4,36	4,24	4,24	4,31	4,40	4,21	4,30	4,24	4,44	4,51	4,67	4,25	4,30	4,37	4,20	4,29	4,25
Max external air temperature (4)	46	46	45	47	47	47	47	44	45	47	47	47	47	46	47	47	45	45
Power supply	400 ± 10% / 3-PE / 50																	
Circuits / Compressors	2/4			2/4			2/4			2/4			2/4			2/4		
Sound power (5)	91,3	83,7	79,3	92,9	85,3	80,6	94,4	86,8	80,7	95,3	87,8	80,7	96,1	88,6	82,5	96,1	88,8	80,6
Sound pressure (6)	63,3	55,7	51,3	64,9	57,3	52,6	66,4	58,8	52,7	67,3	59,8	52,7	68,1	60,6	54,5	68,1	60,8	52,6
Width	2191			2191			2191			2191			2191			2191		
Depth	3091			3091			3091			3439			3439			3465		
Height	2424			2424			2424			2424			2424			2424		
Installed weight	1779			1875			1972			2474			2566			2875		

Models AST2	150			160			170			190			210			240		
Versions	HE	SHE	SSN	HE	SHE	SSN	HE	SHE	SSN	HE	SHE	SSN	HE	SHE	SSN	HE	SHE	SSN
Nominal cooling capacity (1)	396,2	374,8	359,5	429,9	405,5	389,3	477,6	454,1	437,3	525,5	495,3	473,8	586,6	556,7	535,4	644,7	606,9	581,6
Total absorbed power (1)	141,9	147,7	153,8	147,1	153,3	159,1	159,5	163,4	168,3	185,5	193,5	201,8	198,5	204,5	211,6	224,8	236,2	246,6
EER (2)	2,79	2,54	2,34	2,92	2,65	2,45	2,99	2,78	2,60	2,83	2,56	2,35	2,96	2,72	2,53	2,87	2,57	2,36
SEER (3)	4,28	4,34	4,41	4,68	4,72	4,89	4,65	4,82	5,00	4,60	4,65	4,80	4,60	4,69	4,88	4,59	4,63	4,73
Max external air temperature (4)	47	46	47	47	47	47	47	47	47	47	46	47	47	47	47	47	47	47
Power supply	400 ± 10% / 3-PE / 50																	
Circuits / Compressors	2/4			2/6			2/6			2/6			2/6			2/6		
Sound power (5)	97,1	89,8	81,9	94,8	87,5	81,8	95,6	88,2	82,8	96,8	89,4	82,8	98,1	90,8	83,7	99,5	92,2	83,7
Sound pressure (6)	69,1	61,8	53,9	66,8	59,5	53,8	67,6	60,2	54,8	68,8	61,4	54,8	70,1	62,8	55,7	71,5	64,2	55,7
Width	2191			2191			2191			2191			2191			2191		
Depth	4455			4455			5445			5445			6435			6435		
Height	2424			2424			2424			2424			2424			2424		
Installed weight	3420			3371			3934			4136			4861			4923		

Models AST2	270			300			330			360		
Versions	HE	SHE	SSN	HE	SHE	SSN	HE	SHE	SSN	HE	SHE	SSN
Nominal cooling capacity (1)	719,1	679,8	636,1	794	742,7	691,5	883,6	829,5	773,7	944,9	893	834,7
Total absorbed power (1)	251,6	257,5	271,7	276,6	288,3	306,4	313,1	323,5	341,8	337,1	344,9	363,3
EER (2)	2,86	2,64	2,34	2,87	2,58	2,26	2,82	2,56	2,26	2,80	2,59	2,30
SEER (3)	4,69	4,77	4,86	4,80	4,87	4,91	4,69	4,75	4,73	4,72	4,81	4,81
Max external air temperature (4)	47	46	46	47	47	47	47	46	46	47	47	47
Power supply	400 ± 10% / 3-PE / 50											
Circuits / Compressors	2/6			2/6			3/9			3/9		
Sound power (5)	99,0	91,8	86,7	99,8	92,6	87,4	99,7	92,5	87,3	99,7	92,6	87,4
Sound pressure (6)	71,0	63,8	58,7	71,8	64,6	59,4	71,7	64,5	59,3	71,7	64,6	59,4
Width	2191			2191			2191			2191		
Depth	7425			7425			8415			9405		
Height	2513			2513			2513			2513		
Installed weight	5467			5667			6467			6667		

Data declared according to UNI EN 14511:2018. All data refers to standard units without accessories/options which require an electrical feeding source and in nominal working conditions.

- (1) Data referred to nominal conditions, external ambient temperature 35 °C and evaporator water temperature IN/OUT 12/7 °C;
- (2) Data referred to the full load functioning and nominal conditions, external ambient temperature 35 °C and evaporator water temperature IN/OUT 12/7 °C;
- (3) Data declared in compliance with the European Regulation (EU) 2016/2281 with regard to ecodesign requirements for cooling products (air conditioning application);
- (4) Data declared referred to cooling mode and outlet water temperature 7 °C;
- (5) Sound power: determined on the basis of measurements taken in accordance with the standard ISO 3744;
- (6) Sound pressure at 10 m: average value obtained in free field on a reflective surface at a distance of 10 m from the external side of the electrical panel of machine and at height of 1.6 m from the unit support base. Values with tolerance ± 2 dB. The sound levels refer to operation of the unit under full load in nominal conditions and with circulation pump.

The listed noise levels, weights and dimensions refer to base units with no options fitted.



MTA is ISO9001 certified, a sign of its commitment to complete customer satisfaction.



MTA products comply with European safety directives, as recognised by the CE symbol.



MTA participates in the E.C.C. programme for LCP-HR. Certified products are listed on: www.eurovent-certification.com
Certification applied to the units:
- Air/Water up to 600 kW
- Water/Water up to 1500 kW



EAC Declaration

M.T.A. S.p.A.

Business Office
Viale Spagna, 8 - ZI
35020 Tribano (PD) - Italy
Tel. +39 049 9588611
Fax +39 049 9588612
info@mta-it.com
www.mta-it.com



Cooling, conditioning, purifying.